



GG500/GG510/5 Series Electronic Choice

Display With Pulse Output



GG500
Remote
Mount

GG510
Local
Mount



ACCURACY: ± 0.1% OF READING

The GG500 is a remote mount Pulse-Out Transmitter with battery powered display. Choose the GG510 when a local mount is needed.

Features and Benefits:

- ✓ Provides communication with process control equipment.
- ✓ Works with G Series, G2 Turbine Meters and GM Oval Gear Meters.
- ✓ Industry Standard Output: Unscaled Pulse.
- ✓ Easily mounted on pipe or wall.

GG500/GG510 – SPECIFICATIONS

Accuracy:	± 0.1% of reading
Output Options:	
Primary Output:	Open Collector (NPN)
Pulse-Out:	
Max. "OFF" Voltage:	60 V
Max. "ON" Current:	200 mA
Max. "ON" Voltage Drop:	< 0.5 V @ 200 mA
Electrical:	
Strain Relief:	Hubble PG7
Strain Relief Thread:	Female 1/2-20 UNF-2B
Cable:	<i>Remote:</i> Belden 9363 (500 Series only) <i>Local:</i> No cable provided
Cable Length:	20 ft. (6 m) provided (500 Series only)
Power Supply:	9-volt battery or externally powered
Voltage Supply (Min.):	7 VDC
Voltage Supply (Max.):	30 VDC
Input Options:	Hall Effect, Reed Switch, Open Collector or Low Level Sine Wave
Remote Mounting:	Pipe or wall
Operating Temperature:	+14°F to +140°F (-10°C to +60°C)
Frequency Input:	
Low Level Coil (LLC):	0 - 1000 Hz
High Level Low Freq.:	0 - 150 Hz
High Level High Freq.:	0 - 1000 Hz
Enclosure Rating:	NEMA 4X / IP55
Shipping Weight:	<i>Remote:</i> 2.0 lbs. (.90 kg) <i>Local:</i> 1.0 lbs. (.45 kg)
Calibrateable:	K-factor Entry

APPROVALS



BUY SMART. BUY VALUE. BUY